

CF-222

QINOO® REGULAR BLACK

HIGH BLACK

MEDIUM BLACK

REGULAR BLACK

CONTACT DETAILS

✉ export@qinoocarbon.com

☎ +86-21-64814142

🌐 www.qinoocarbon.com

📞 +86 13310109028 (CN)
+86 17359233301 (EN)

PIGMENT CARBON BLACK CF-222

PROPERTY

CF-222 has high purity, strong tinting strength, easy dispersion, smooth surface of the extrudate (no need to do pre-dispersing treatment), blue tone and UV resistance.

APPLICATION

This product can be widely used in various fields of plastic industry, PVC, PP, PE, advanced cable sheath, cable shielding materials, and various plastic accessories.

REPLACEMENTS

HB-10 (Degussa)

SPECIFICATION

Surface Area	M ² /g	140
DBP	ml/100g	95
Tinting Strength	%	115
Ash Content	%, max	0.02
PH Value		7.5
Sieve Residue	45μm, ppm max	10
Pour Density	kg/m ³	350
Heating Loss	%, max	1.0
Blackness	MY, max	30/255



SHANGHAI QINOO CHEMICAL CO.,LTD.

19 / F, BLDG E, No.585, Lingling Road, Xuhui District, Shanghai, China