

# CF-611

QINOO® REGULAR BLACK


HIGH BLACK


MEDIUM BLACK


 REGULAR BLACK

## CONTACT DETAILS

 [export@qinoocarbon.com](mailto:export@qinoocarbon.com)

 +86-21-64814142

 [www.qinoocarbon.com](http://www.qinoocarbon.com)

 +86 13310109028 (CN)  
+86 17359233301 (EN)

## PIGMENT CARBON BLACK CF-611

### PROPERTY

CF-611 has high purity, strong tinting strength, easy dispersion, smooth surface of the extrudate (no need to do pre-dispersing treatment), blue tone and UV resistance.

### APPLICATION

This product can be widely used in various fields of plastic industry, such as PVC, PP, PE, high-end cable sheath, cable shielding material, cement sealant, foaming EVA, and various plastic accessories.

### REPLACEMENTS

HB-20 (Degussa)

### SPECIFICATION

Surface Area	M <sup>2</sup> /g	140
DBP	ml/100g	96
Tinting Strength	%	140
Ash Content	%, max	0.02
PH Value		1.85
Sieve Residue	45μm, ppm max	10
Pour Density	kg/m <sup>3</sup>	350
Heating Loss	%, max	2.08
Blackness	MY, max	18/260



**SHANGHAI QINOO CHEMICAL CO.,LTD.**

19 / F, BLDG E, No.585, Lingling Road, Xuhui District, Shanghai, China